Cellux®
SINCE 1922

PAINTER´S TAPE



C-576

BLUE MASKING TAPE

DESCRIPTION

The painter's **C-576 masking tape** is a medium-density crepe paper tape designed to removes cleanly even in direct sunlight and delivers professional paint results at an exceptional value.

They are ideal for protecting surfaces in work with paintings guaranteeing a quality finish.

USES

- Ideal for the professional paint industry due to its resistance to all types of paints and solvents.
- Architecture, marquetry and labeling.
- Masking and protection multiple surfaces such as: wall, wood, plastic, steel, glass, windows, doors, trim, others.

FEATURES

- UV Resistant
- Clean removal
- No paint bleed
- Easy to tear
- Removes cleanly for up to 14 days
- Cleaner paint lines

TECHNICAL DATA

Property	Standard
Backing	Crepe paper
Adhesive	Synthetic rubber-Based adhesive
Thickness	5,9 mils
Adhesion to Stainless Steel	25 lbs/in width
Tensile Strength	14 lbs/in width
Temperature range	50 F to 212 F

STORAGE CONDITIONS

Tape storage guidelines recommend keeping it in its original packaging, ensuring a cool and dry environment, away from direct sunlight. It is advisable to utilize the tape within 12 months from the date of shipment. Moreover, when applying the tape, ensure that the surfaces are clean, dry, and devoid of any grease, oil, or other contaminants.

HOW TO USE

1. Clean the surface.
2. Unroll, cut if necessary and apply.
3. Apply pressure with your hand reinforcing the adhesion.

* Be sure to remove the tape once the paint is dry and the job is finished.

SIZE

Widths (in)	Lengts (yd)
3/4	60
1	60
1,5	60
2	60
3	60

At **Cellux** we understand that each project is different. We can manufacture the size according to your requirement.

"INNOVATIVE ADHESIVE TAPE SOLUTIONS FOR EVERY INDUSTRY."



CELLUX US LLC / LOT 73, 3042 NW 73RD ST, UNIT 2 MIAMI, FL 33147 / **PHONE +1 (754) 248-3621**

REGISTERED TRADEMARK OF CELLUX US