Cellux®
SINCE 1922

RED STUCCO TAPE

C-792



DESCRIPTION

The **red stucco tape C-792** is essential for installing stucco cement, masonry, insulation, and other components during construction projects. When they are dedicated to these applications, having high-quality stucco tape for builders marks a significant difference in effectiveness and efficiency when contractors can complete their work.

USES

- Stucco and plastering: Masking off windows, doors, walls, and other surfaces during stucco or plastering applications.
- Exterior painting: Creating clean paint lines and protecting surfaces from overspray or paint splatter during exterior painting projects.
- Weather-resistant applications: Providing a durable and waterproof barrier in outdoor construction or renovation projects.

FEATURES

- High durability making it suitable for demanding applications.
- Resistant UV and moisture.
- It is flexible.
- Clean removal.
- Superior strength.

TECHNICAL DATA

Property	Standard
Backing	Polyethylene film
Adhesive	Synthetic rubber-based
Thickness	6,9 mils
Tensile Strength vertical	19 (lb/in2)
Adhesion to steel	5.6 (lb/in)
Elongation at break-vertical	300%
Elongation ar break-horizontal	500%
Indoor/Outdoor	Indoor and outdoor

STORAGE CONDITIONS

Tape storage guidelines recommend keeping it in its original packaging, ensuring a cool and dry environment, away from direct sunlight. It is advisable to utilize the tape within 12 months from the date of shipment. Moreover, when applying the tape, ensure that the surfaces are clean, dry, and devoid of any grease, oil, or other contaminants.

HOW TO USE

1. Clean the surface.
2. Unroll, cut if necessary and apply.
3. Apply pressure with your hand reinforcing the adhesion.

SIZE

Widths (in)	Lengts (yd)
2	55

At **Cellux** we understand that each project is different. We can manufacture the size according to your requirement.

"INNOVATIVE ADHESIVE TAPE SOLUTIONS FOR EVERY INDUSTRY."

AMERICAN QUALITY

cellux.us

CELLUX US LLC / LOT 73, 3042 NW 73RD ST, UNIT 2 MIAMI, FL 33147 / **PHONE +1 (754) 248-3621**

REGISTERED TRADEMARK OF CELLUX US