Cellux®
SINCE 1922

AUTOMOTIVE TAPE



C-584

YELLOW MASKING TAPE

DESCRIPTION

The **industrial yellow masking tape C-584** is ideal for perfect automotive and marine projects. The tape's professionals prefer our tape to delineate edges and protect surfaces from difficult access or surfaces in extreme conditions. Thanks to its flexibility, it allows you to make figures of all kinds, facilitating the painting operation.

USES

- Ideal for the professional industrial painters.
- Two-tone color application.
- Masking and protection multiple surfaces such as: metal, rubber, glass and plastic.
- Applicable in automotive and marine paint jobs that require flexibility for fine lines.

FEATURES

- High temperature
- Clean removal
- No paint bleed
- Remove in one piece
- Improves visibility
- Cleaner paint lines

TECHNICAL DATA

Backing	Crepe paper
Adhesive	Special Rubber-based adhesive
Thickness	5.9 mils
Adhesion to stainless steel	1.4 lbs/in width
Tensile strength	11.5 lbs/in width
Temperature range	50 F to 302 F

STORAGE CONDITIONS

Tape storage guidelines recommend keeping it in its original packaging, ensuring a cool and dry environment, away from direct sunlight. It is advisable to utilize the tape within 12 months from the date of shipment. Moreover, when applying the tape, ensure that the surfaces are clean, dry, and devoid of any grease, oil, or other contaminants.

HOW TO USE

Clean the surface. 1

Unroll, cut if necessary and apply. 2

Apply pressure with your hand 3 reinforcing the adhesion.

* Be sure to remove the tape once the paint is dry and the job is finished.

SIZE

Widths (in)	Lengts (yd)
1/2	60
1	60
1 1/2	60
2	60
3	60

At **Cellux** we understand that each project is different. We can manufacture the size according to your requirement.

"INNOVATIVE ADHESIVE TAPE SOLUTIONS FOR EVERY INDUSTRY."



CELLUX US LLC / LOT 73, 3042 NW 73RD ST, UNIT 2 MIAMI, FL 33147 / **PHONE +1 (754) 248-3621**

REGISTERED TRADEMARK OF CELLUX US